


# B56

## 3MP Indoor Fisheye Dome with D/N, Superior WDR, Fixed lens




- 3 Megapixel
- Day & Night
- Hemispheric Fisheye Lens with f1.19mm/ F2.0
- Superior WDR (107 dB)
- 15 fps at 2048 x 1536

### PHOTO INDICATION



- |                          |                       |
|--------------------------|-----------------------|
| 1 Ethernet Port          | 5 Audio output        |
| 2 Power LED              | 6 MicroSDHC Card Slot |
| 3 Digital Input & Output | 7 DC 12V Power Input  |
| 4 Audio Input            | 8 Reset Button        |

### DIMENSION DIAGRAM



Unit: mm [inch]

### ACCESSORY OPTIONS

Popular Mounting Solutions	
Flush	PMAX-1009 
Wall	PMAX-0310 
Pendant	PMAX-0101 PMAX-0103 
Pole	PMAX-0101 PMAX-0303 PMAX-0503 

\* For more mounting solutions, please refer to Project Planner on [www.acti.com](http://www.acti.com)

**PRODUCT SPECIFICATION****B56****• Device**

Product Type	Indoor Fisheye Dome
Image Sensor	Progressive Scan CMOS
Sensor Size	1/3"
Day / Night	Yes
Superior Low Light Sensitivity	No
Minimum Illumination	Color: 0.1 lux at F2.0 (30 IRE, 2400°K); B/W: 0.05 lux at F2.0 (30 IRE, 2400°K)
Color to B/W switch	ISP based switch, configurable
Mechanical IR Cut Filter	Yes
IR Sensitivity Range	700 - 1100nm
IR LED	No
Electronic Shutter	1/5 ~ 1/2,000 sec (manual mode); 1/5 ~ 1/10,000 sec (auto mode)

**• Lens**

Focal Length / Aperture	Fixed (Fisheye lens), f1.19 mm / F2.0
Iris	Fixed iris
Focus	Fixed Focus
Mount Type	Board Mount
Horizontal Viewing Angle	180°

**• Video**

Compression	H.264, MJPEG
Maximum Frame Rate vs. Resolution	15 fps at 2048 x 1536; 15 fps at 640 x 480; 15 fps 320 x 240
Mode	Fisheye view, 180° /360° Panorama, ePTZ
Multi-Streaming	Simultaneous dual streams based on two configurations
Bit Rate	28 Kbps - 6 Mbps (per stream)
Bit Rate Mode	Constant, Variable
Image Enhancement	Superior WDR (107 dB); White balance: automatic, hold and manual; Brightness; Contrast; Sharpness (auto); Automatic gain control; Digital noise reduction; Flickerless
Privacy Mask	4 configurable regions
Text Overlay	User defined text on video
Image Orientation	Image flip and mirror

**• Audio**

Compression	8 kHz, Mono, PCM, 16 bit encoding; G.711
Audio-In	Cable with 3.5mm Phone Jack
Audio-Out	Cable with 3.5mm Phone Jack

**• Network**

Protocol & Service	TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour
Ethernet Port	1, Ethernet (10/100 Base-T), RJ-45 connector
Security	IP address filtering; HTTPs encryption; Password protected user levels; Anonymous login; IEEE802.1X network access control

**• Alarm**

Alarm Trigger	Video motion detection (3 regions); External device through digital input
Alarm Response	Notify control center; Change camera settings; Command other devices; E-mail notification with snapshots; Save video or snapshot to local storage; Upload video, snapshot to FTP server; Activate external device through digital output

**• Interface**

Digital Input	1, terminal block
Digital Output	1, terminal block
Local Storage	MicroSDHC memory card slot (card not included)

**• General**

Power Source / Consumption	PoE Class 2 (IEEE 802.3af) / 4.5 W; DC 12V / 3.5 W
Weight	338 g (0.75 lb)
Dimensions (Ø x H)	150mm x 48mm (5.91" x 1.90")
Mount Type	Surface, Pendant, Wall, Corner, Pole, Flush, Gang Box
Starting Temperature	-10 °C - 50°C (14°F - 122°F)
Operating Temperature	-10 °C - 50°C (14°F - 122°F)
Operating Humidity	10% ~ 85% RH
Approvals	CE (EN 55022 Class B, EN 55024), FCC (Part15 Subpart B Class B)

**• Integration**

Unified Solution	Fully compatible with ACTi software
ISV Integration	Software Development Kit (SDK) available ; ONVIF compliant
Firmware Access Browser	Microsoft Internet Explorer 8.0 or newer (full functionality); Other browsers with VLC installed (partial functionality)

\* All specifications are subject to change without notice.

\* All brand names and registered trademarks are the property of their respective owners.

[www.acti.com](http://www.acti.com)